

PRODUCT SPECIFICATION

Opaque White Permanent

Description

- White, high bulk, woodfree, filled, uncoated 70gsm.
- Coating under adhesive to give high opacity and 'block-out' effect
- Aqueous acrylic emulsion adhesive.
- Minimum application temperature: +5°C
- Temperature range: -20°C to +100°C
- Chill grade - ideal for chilled food labelling.

Very good heat resistance which enables trouble free performance in different hot fusing print processes. Good adhesion to cardboard and low energy (e.g. plastic bags) surfaces. Good 'all round' permanent adhesive. Approved for indirect food contact. The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations. No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

Laminate Information

Thickness: 163 mic Weight: 140 gsm

Backing

White high density kraft paper with excellent lay flat properties

Printing Compatability

DRY TONER	LITHO PRINT	InkJet PRINT	LASER PRINT
PCL A4+ Digital Office A3 SRA3 SRA3+	PCL A4+ Digital Office A3 SRA3 SRA3+	PCL A4+ Digital Office A3 SRA3 SRA3+	PCL A4+ Digital Office A3 SRA3 SRA3+

For detailed printing information please refer to our 'Printing Guidelines'

PCL
by
avery